Author Index

Adey, R. A.	Development of analysis tools for spline couplings	347–357
Agrawal, B. N.	Active vibration suppression of a flexible structure using smart material and a modular control patch	217–229
Allen, C. B.	CHIMERA volume grid generation within the EROS code	125–141
Babu, K. K. R.	Dynamics of nose cone jettisoning from spinning rockets	327–345
Barrett, R. V.	Transition detection for laminar flow aircraft using microphones beneath the surface of laser drilled suction panels	143–155
Barrett, R. V.	Investigation of the separation bubble formed behind the sharp leading edge of a flat plate at incidence	157–176
Baynham, J.	Development of analysis tools for spline couplings	347–357
Becker, A. A.	A three-dimensional finite element investigation of the bolt stresses in an aero-engine Curvic coupling under a blade release condition	231–245
Bond, I.	Aerodynamic and structural design of a solar-powered micro unmanned air vehicle	97–106
Bray, T. P.	On the velocity profile of inclined jets in a boundary layer for vorticity production	55–64
Bruce, P. D.	Modelling and identification of non-linear aerodynamic functions using B-splines	27–40
Butler, I. G.	A quasi-three-stage space-qualified passive radiator system for cooling a detector array to −150 °C	195–205
Chiesa, S.	The double-fuselage layout: a preliminary case study of a possible way of reducing the development costs for new high-capacity aircraft	85–95
Crompton, M. J.	Investigation of the separation bubble formed behind the sharp leading edge of a flat plate at incidence	157–176
Datta, P. K.	Dynamic instability of laminated composite rectangular plates subjected to non-uniform harmonic in-plane edge loading	295–312
Di Sciuva, M.	The double-fuselage layout: a preliminary case study of a possible way of reducing the development costs for new high-capacity aircraft	85–95
Ebrahimi, M.	Aircraft pitch and heave rate control	1–8
Esposito, A.	Recasting the Fay–Riddell formulae for computing the stagnation point heat flux	115–120
Gaerke, J.	Life enhancement of fatigue-aged fastener holes using the cold expansion process	281–293
Garry, K. P.	On the velocity profile of inclined jets in a boundary layer for vorticity production	55–64
Goodall, C. V.	A quasi-three-stage space-qualified passive radiator system for cooling a detector array to −150 °C	195–205
Hashemi, S. M. R.	A systematic approach to aircraft crashworthiness and impact surface material models	265–280
Hyde, T. M.	A three-dimensional finite element investigation of the bolt stresses in an aero-engine Curvic coupling under a blade release condition	231–245
Kellett, M. G.	Modelling and identification of non-linear aerodynamic functions using B-splines	27–40
Lee, Y.-Y.	Vibration control of composite plates under random loading using piezoelectric material	9–25
Lin, S.-C.	Sensitivity of the dynamic behaviour of random rotating Timoshenko beams to system parameter changes	247–259
Lindstedt, R. P.	The modelling of direct chemical kinetic effects in turbulent flames	177–189
Lochan, R.	Dynamics of nose cone jettisoning from spinning rockets	327–345
Maggiore, P.	The double-fuselage layout: a preliminary case study of a possible way of reducing the development costs for new high-capacity aircraft	85–95
Mehta, R. C.	Numerical simulation of high-speed turbulent reacting coaxial jet flow using a structured grid	359–368
Nelson, P. A.	Fast boundary layer suction optimization with neural networks	107–113
Ng, C.-F.	Vibration control of composite plates under random loading using piezoelectric material	9–25
Nutbean, J.	Aerodynamic and structural design of a solar-powered micro unmanned air vehicle	97–106
Panting, J. R.	Thermodynamic studies of a novel aeroengine concept	71–83
Pullen, K. R.	Thermodynamic studies of a novel aeroengine concept	71–83
Richardson, I. J.	A three-dimensional finite element investigation of the bolt stresses in an aero-engine Curvic coupling under a blade release condition	231–245
Sachs, G.	Longitudinal flightpath predictor design for minimum pilot compensation	41–53

© IMechE 2000

Sahu, S. K.	Dynamic instability of laminated composite rectangular plates subjected to non-uniform harmonic in-plane edge loading	295–312
Schmidt, S. P.	Active vibration suppression of a flexible structure using smart material and a modular control patch	217–229
Song, F.	An autonomous navigation scheme using global positioning system/geomagnetism integration for small satellites	207–215
Song, G.	Active vibration suppression of a flexible structure using smart material and a modular control patch	217–229
Taylor, J. W.	A three-dimensional finite element investigation of the bolt stresses in an aero-engine Curvic coupling under a blade release condition	231–245
Taylor, J. W.	Development of analysis tools for spline couplings	347–357
Walton, A. C.	A systematic approach to aircraft crashworthiness and impact surface material models	265–280
Wang, Z.	Life enhancement of fatigue-aged fastener holes using the cold expansion process	281–293
Welch, C. S.	Ascending node alteration of polar orbiting spacecraft using low-thrust propulsion	313–321
Whalley, R.	Aircraft pitch and heave rate control	1–8
Wilson, C.	Aerodynamic and structural design of a solar-powered micro unmanned air vehicle	97–106
Wright, M. C. M.	Fast boundary layer suction optimization with neural networks	107–113
Ye, Z.	The bending of composite shallow revolutional shells	369–376
Zhang, X.	Life enhancement of fatigue-aged fastener holes using the cold expansion process	281–293
Zhou, Z.	The bending of composite shallow revolutional shells	369–376
Zuo, W.	An autonomous navigation scheme using global positioning system/geomagnetism integration for small satellites	207–215
Zuppardi, G.	Recasting the Fay–Riddell formulae for computing the stagnation point heat flux	115–120

© IMechE 2000